



PJ, Maxx-D, Lone Star Series



Specifications:

- 3" x 3.5lb Channel x-member on 18" centers
- 2" x 3" x 3/16" Structural tubing main rails
- 2" x 3" x 1/8" Structural tubing side top rails
- 2" x 3" x 1/8" Structural tubing door frame
- 8" x 8" Rear wheels w/ greasable axles
- 5" HD pipe front wheels w/ greasable axles
- (2) Heavy Duty greasable hinges
- (2) 3/8" Plate slam latches with line up plates
- 1" Pull D-ring
- 3/16" Formed rear corner post
- Tarp Hooks on sides, fronts, and doors

	Standard	Med Duty	Heavy Duty
Floor sheet	10ga	10ga	7ga
Wall sheet	12ga	10ga	10ga

Other Options

- Barn Doors
- Tarp, lids, roof options
- Rubber wheels

Features and Benefits:

- Designed to roll-off, industry standards to extend life of container
- Nestable tub design to minimize freight cost
- Front and rear corners are ground smooth to prevent tarp damage
- Front corner wraps installed and solid welded to prevent separation of side walls and front
- Rear corner post design prevents spreading of rear walls
- Exterior walls are welded solid exterior and skip welded inside preventing premature failures
- Cam latch, safety chains, and greasable 1/2" plate hinges ensure door securement and alignment
- All roller axles are greasable to prevent premature wearing of critical parts
- Containers fully primed with exterior painted to prevent premature rusting
- Pricing includes any color!

